



R-Loc® Roller Ball Ties - Polyester Coated - SS 316



Regular - 4,6 mm wide

MS Art.no.	EL no.	Part no.	Length mm	Width mm	Metal Thickness mm
BC-046-0100	Pending	BC46-100	100	4.6	0.25
BC-046-0150	Pending	BC46-150	150	4.6	0.25
BC-046-0200	Pending	BC46-200	200	4.6	0.25
BC-046-0360	Pending	BC46-360	360	4.6	0.25
BC-046-0520	Pending	BC46-520	520	4.6	0.25
BC-046-0680	Pending	BC46-680	680	4.6	0.25
BC-046-0840	Pending	BC46-840	840	4.6	0.25
BC-046-1000	Pending	BC46-1000	1000	4.6	0.25

Heavy Duty - 7,9 mm wide

MS Art.no.	EL no.	Part no.	Length mm	Width mm	Metal Thickness mm
BC-076-0100	Pending	BC76-100	100	7,9	0.25
BC-076-0150	Pending	BC76-150	150	7,9	0.25
BC-076-0200	Pending	BC76-200	200	7,9	0.25
BC-076-0360	Pending	BC76-360	360	7,9	0.25
BC-076-0520	Pending	BC76-520	520	7,9	0.25
BC-076-0680	Pending	BC76-680	680	7,9	0.25
BC-076-0840	Pending	BC76-840	840	7,9	0.25
BC-076-1000	Pending	BC76-1000	1000	7,9	0.25



Technical information:

Material:	316 grade non-magnetic stainless steel
Temperatur Range:	-80°C to +150°C
Coating:	Pure Polyester
Flammability Rating:	Fireproof, Halogen Free and UV-resistant
Loop Tensile Strength:	4,6 mm width: 445 N (100lb) 7,9 mm width: 1112 N (250lb)
Approvals:	DNV Cert. no.E-9145, UL-listed E227552
Manufacturer:	Raychem RPG Ltd.

