



R-Loc® Roller Ball Ties - Uncoated - SS 316



Regular - 4,6 mm wide

MS Art.no.	EL no.	Part no.	Length mm	Width mm	Metal Thickness mm
BU-046-0100	Pending	BU46-100	100	4.6	0.25
BU-046-0150	Pending	BU46-150	150	4.6	0.25
BU-046-0200	Pending	BU46-200	200	4.6	0.25
BU-046-0360	Pending	BU46-360	360	4.6	0.25
BU-046-0520	Pending	BU46-520	520	4.6	0.25
BU-046-0680	Pending	BU46-680	680	4.6	0.25
BU-046-0840	Pending	BU46-840	840	4.6	0.25
BU-046-1000	Pending	BU46-1000	1000	4.6	0.25

Heavy Duty - 7,9 mm wide

MS Art.no.	EL no.	Part no.	Length mm	Width mm	Metal Thickness mm
BU-076-0100	Pending	BU76-100	100	7,9	0.25
BU-076-0150	Pending	BU76-150	150	7,9	0.25
BU-076-0200	Pending	BU76-200	200	7,9	0.25
BU-076-0360	Pending	BU76-360	360	7,9	0.25
BU-076-0520	Pending	BU76-520	520	7,9	0.25
BU-076-0680	Pending	BU76-680	680	7,9	0.25
BU-076-0840	Pending	BU76-840	840	7,9	0.25
BU-076-1000	Pending	BU76-1000	1000	7,9	0.25



Technical information:

Material: 316 grade non-magnetic stainless steel
Temperatur Range: -80°C to +500°C
Coating: N.A.
Flammability Rating: Absolutely Fireproof and UV-resistant
Loop Tensile Strength: 4,6 mm width: 445 N (100lb)
 7,9 mm width: 1112 N (250lb)
Approvals: DNV Cert. no.E-9145, UL-listed E227552
Manufacturer: Raychem RPG Ltd.

